



US LUBE DYNAMICS SYN LE

Fully synthetic passenger car motor oil formulated with a proprietary blend of high performance synthetic basestocks and Polyalphaolefins (PAO) fortified with a precisely balanced additive component system. The low viscosity, fully synthetic formulation helps to increase engine efficiency and offers outstanding fuel economy.

This oils provide maximum engine performance from today's latest technology, highly engineered engines that operate with tighter tolerances, requiring a high level of protection and low viscosity oils.

Properties

- > Independently proven to improve engine efficiency
- > Outstanding low temperature capabilities
- > Outstanding thermal and oxidation stability
- > Sustains maximum performance even when under pressure

Specifications & Recommendations

- > API SP
- > API A5/B5
- > ACEA C2
- > ILSAC GF-6
- > BMW LL-12 FE
- > FORD WSS-M2C950-A
- > MERCEDES BENZ MB 227.61
- > MERCEDES BENZ MB 229.61

Typical Specifications

Test Description	Method	Unit	
SAE Viscosity Grade	SAE J 300	-	0W30
Density @ 15 °C	ASTM D 4052	kg/L	0.8470
Flash Point	ASTM D 92	°C	216
Pour Point	ASTM D 97	°C	-42
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	63.15
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	11.1
Viscosity Index	ASTM D 2270	-	170
TBN	ASTM D 2896	mgKOH/g	9.4
CCS	ASTM D 5293	cP	≤6200
HTHS	ASTM D 5481	cP	≥2.9

www.uslube-chicago.com

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranted of MERCHANTABILITY and FITNESS.